
Mash the Throttle

A Free Project Sheet
NOT FOR RESALE

By Duncan Macdougal



Skill Level: Advanced Beginner




Monster Rally
Finished Quilt Size: 56" x 65"
(142.24 cm x 165.10 cm)
www.3wishesfabric.com
Please check our website for pattern updates before starting this project.


Fabrics in the Mash the Throttle Collection



Full Throttle 22988-WHT-CTN-D



Monster Truck Outline 22989-TRQ-CTN-D



Final Lap 22990-WHT-CTN-D



Tread Marks 22991-BLK-CTN-D



Camo Tracks 22992-MLT-CTN-D



Solid Black



Solid Gray

Solid White

Page 3

Materials

Matchais		
1 3/4 yards (1.60m)	Tread Marks (A)	
•	22991-BLK-CTN-D	
½ yard (0.46m)	Camo Tracks (B)	
	22992-MLT-CTN-D	
1 % yards (1.49m)	Solid White (C)	
¹ / ₃ yards (0.31m)	Solid Gray (D)	
½ yards (0.12m)	Solid Black (E)	
% yard (0.81m)	Final Lap (F)*	
	22990-WHT-CTN-D	
1 yard (0.92m)	Monster Truck Outline (G)	
	22989-TRQ-CTN-D	
1 ² / ₃ yards (1.53m)	Full Throttle (H)	
	22988-WHT-CTN-D	
3 ³ / ₄ yards (3.43m)	Full Throttle (Backing)	
	22988-WHT-CTN-D	

^{*}Includes binding

You will also need:

• Fusible web

Cutting Instructions

Please note: All strips are cut across the width of fabric (WOF) from selvage to selvage edge unless otherwise noted.

From the Tread Marks (A), cut:

- (3) 12 1/4" x WOF strips. Sub-cut (9) 12 1/4" squares. From each square cut (1) 8 ½"square on-point (Fig. 1).
- See instructions to cut (15) Tires.

From the Camo Tracks (B), cut:

• (3) 5" x WOF strips. Sub-cut (18) 5" squares.

From the Solid White (C), cut:

- (4) 8 ½" x WOF strips. Sub-cut (15) 8 ½" squares.
- (4) 2 ½" x WOF strips.
- (3) 1 ½" x WOF strips. Sew the strips together end to end with diagonal seams and cut (2) 1 ½" x 55 ½" strips.
- (3) 1 ½" x WOF strips. Sew the strips together end to end with diagonal seams and cut (2) 1 ½" x 48 ½" strips.

From the Solid Gray (D), cut:

• See instructions to cut (15) Rims.

From the Solid Black (E), cut:

• See instructions to cut (15) Rim Centers.

From the Final Lap (F), cut:

- (4) 2 ½" x WOF strips.
- (7) 2 ½" x WOF strips for the binding.

From the Monster Truck Outline (G), cut:

- (6) 1 ½" x WOF strips. Sub-cut (24) 1 ½" x 8 ½" strips.
- (6) 1 ½" x WOF strips. Sew the strips together end to end with diagonal seams and cut (5) 1 ½" x 44 ½" strips.
- (3) 1 ½" x WOF strips. Sew the strips together end to end with diagonal seams and cut (2) 1 ½" x 53 ½" strips.
- (3) 1 ½" x WOF strips. Sew the strips together end to end with diagonal seams and cut (2) 1 ½" x 46 ½" strips.

From the Full Throttle (H), cut:

- (2) 4 ½" x 57 ½" Length of Fabric (LOF) strips.
- From the remaining fabric cut (2) 4 ½" x 56 ½" WOF strips, piece as needed.

From the Full Throttle (Backing), cut:

• (2) 64" x WOF strips for the backing. Sew the strips together and trim to make the 64" x 73" back.

Block Assembly

Note: The arrows in figures represent the fabric print direction. Pay attention to the fabric and unit orientations when assembling the various components. Use a 1/4" seam allowance with right sides together (RST) unless otherwise noted.

1. Place (1) 5" Fabric B square on the top left corner of (1) 8 ½" Fabric A square, right sides together (Fig. 2). Sew across the diagonal of the smaller square from the upper right corner to the lower left corner (Fig. 2). Flip open the triangle formed and press. Trim away the excess fabric from behind the triangle 1/4" away from the sewn seam (Fig. 3).





Fig. 2

- 2. Follow Figure 4 for the seam direction to add a 5" Fabric B square to the lower right corner of the 8 ½" Fabric A square to make (1) 8 ½" Block One square (Fig. 5).
- 3. Repeat Steps 1-2 to make (9) Block One squares total.






Fig. 4


- 4. Following the manufacturer's instructions, trace the listed number of each template onto the paper side of the fusible web. Roughly cut out each template about 1/8" outside the drawn lines.
- 5. Press each template onto the wrong side of the fabrics as listed on the templates. Cut out each template on the drawn lines.


Block Two

make 15

Fig. 6

- 6. Refer to Figure 6 to center and press (1) Fabric D Rim, (1) Fabric A Tire and (1) Fabric E Rim Center onto (1) 8 ½" Fabric C square.
- 7. Finish the raw edges of each shape with a decorative stitch such as a buttonhole or satin stitch to make (1) 8 ½" Block Two square (Fig. 6).
- 8. Repeat Steps 6-7 to make (15) Block Two squares total.
- 9. Sew together (2) 2 ½" x WOF Fabric F strips and (2) 2 ½" x WOF Fabric C strips, lengthwise and alternating them from left to right, to make (1) Strip Set 1 (Fig. 7). Repeat to make a second Strip Set 1.
- 10. From the (2) Strip Set 1's cut (24) 8 ½" x 2 ½" Unit 1 strips (Fig. 8).






Page 4

11. Sew together (4) Unit 1 strips lengthwise to make (1) 8 ½" Block Three square (Fig. 9). Repeat to make (6) Block Three squares total.

Blo	ock	Thr	ee
make 6			
	Un	it 1	
	ſ Ji	uη	
	Un	it 1	
	۱ij	սՈ	
т.	•		

Fig. 9

- 12. Sew together (1) Block One square, (1) 1 ½" x 8 ½" Fabric G strip, (1) Block Two square, (1) 1 ½" x 8 ½" Fabric G strip, (1) Block One square, (1) 1 ½" x 8 ½" Fabric G strip, (1) Block Two square, (1) 1 ½" x 8 ½" Fabric G strip and (1) Block One square, in that order from left to right, to make Row One (Fig. 10). Repeat to make Row Three and Row Five. Pay attention to the Block One orientations.
- 13. Sew together (1) Block Two square, (1) 1 ½" x 8 ½" Fabric G strip, (1) Block Three square, (1) 1 ½" x 8 ½" Fabric G strip, (1) Block Two square, (1) 1 ½" x 8 ½" Fabric G strip, (1) Block Three square, (1) 1 ½" x 8 ½" Fabric G strip and (1) Block Two square, in that order from left to right, to make Row Two (Fig. 10). Repeat to make Row Four and Row Six.
- 14. Sew together the (6) pieced Rows in numerical order and (5) 1 ½" x 44 ½" Fabric G strips, lengthwise and alternating them from top to bottom, to make the 44 ½" x 53 ½" Center Block (Fig. 10).




Page 5


Quilt Top Assembly


(Follow the Quilt Layout while assembling the quilt top.) 15. Sew (1) 1 ½" x 53 ½" Fabric G strip to each side of the Center Block. Sew (1) 1 ½" x 46 ½" Fabric G strip to the top and bottom of the Center Block.

- 16. Sew (1) 1 ½" x 55 ½" Fabric C strip to each side of the Center Block. Sew (1) 1 ½" x 48 ½" Fabric C strip to the top and bottom of the Center Block.
- 17. Sew (1) 4 ½" x 57 ½" Fabric H strip to each side of the Center Block. Sew (1) 4 ½" x 56 ½" Fabric H strip to the top and bottom of the Center Block to make the quilt top.
- 18. Layer and quilt as desired.
- 19. Sew the (7) 2 ½" x WOF Fabric F strips together, end to end with 45-degree seams, to make the binding. Fold this long strip in half lengthwise with wrong sides together and press.
- 20. Bind as desired.



Quilt Layout





Every effort has been made to ensure that all projects are error free. All the information is presented in good faith, however no warranty can be given nor results guaranteed as we have no control over the execution of instructions. Therefore, we assume no responsibility for the use of this information or damages that may occur as a result. When errors are brought to our attention, we make every effort to correct and post a revision as soon as possible. Please make sure to check www.3wishesfabric.com for pattern updates prior to starting the project. We also recommend that you test the project prior to cutting for kits. Finally, all free projects are intended to remain free to you and are not for resale.