



Finished Quilt Size: **52 x 70" (1.32m x 1.78m)** Finished Block Size: **6 x 6" (15.24cm x 15.24cm)** Fabric Collection and Fabric Designer: **Instagram Famous by Kayomi Harai** Technique: **Pieced** Designed by: **Lisa Swenson Ruble** Skill Level: **Advanced Beginner** Tech Edited by: **Quilt Pattern Writers**



Fabric Requirements

DESIGN	COLOR	ITEM ID	YARDAGE
(A) Sushi Cats	Navy	8062-77	½ yard (0.46m)
(B) Colorful Fish	Black	8063-99	1¾ yards (1.26m)
(C) Tossed Cats	White	8064-01	⅓ yard (0.30m)
(D) Packed Cats	Cream	8065-44	⅓ yard (0.30m)
(E) Houndstooth	Black	8066-99*	1⅔ yards (1.52m)
(F) 8 9.5x9 Blocks 24 inch Panel	Black	8068P-99	⅔ yard (0.61m)
(G) Just Color!	Grass	1351-Grass	¾ yard (0.34m)
(H) Just Color!	Orange	1351-Orange	½ yard (0.46m)
(I) Just Color!	Teal	1351-Teal	¾ yard (0.69m)
* includes binding			
(A) (B) (C)	(D) (E) (F)	(G) (H) (l)
Backing (Purchased Separately)			
44" (1.12m) wide Sushi Cats OR	Navy	8062-77	4 yards (3.66m)
108" (2.74m) wide			2 yards (1.83m)



Backing 44"

Additional Materials:

- 100% cotton thread in colors to match
- Batting 60" x 78" (1.52m x 1.98m)



Cutting

Notes:

- Please make sure to check *studioefabrics.net* for pattern updates prior to starting the project.
- All strips are cut across the width of fabric (WOF) from selvage to selvage edge unless otherwise noted.

Fabric A, cut:

(2) 6½" x WOF; subcut (8) 6½" squares

Fabric B, cut:

(2) 6½" x WOF; subcut

(12) 6½" squares(6) 4½" x WOF; sew strips together end to end with diagonal seams, subcut

(2) 4½" x 62½"

(2) 4½" x 52½"

Fabric C, cut:

(1) 6½" x WOF; subcut (6) 6½" squares

Fabric D, cut:

(1) 6½" x WOF; subcut (4) 6½" squares

Fabric E, cut:

(6) 3½" x WOF; subcut (64) 3½" squares

(2) 3" x WOF

(2) 3" x WOF; subcut

(2) 3" x 28½"

(7) 2¹/₂" x WOF for the binding

Fabric F, cut: Trim to measure 23½" x 42½"

Fabric G, cut:

(6) 1½" x WOF; sew strips together end to end with diagonal seams, subcut

- (2) 1½" x 60½"
- (2) 1½" x 44½"

Fabric H, cut:

(3) 2¹/₂" x WOF; sew strips together end to end with diagonal seams, subcut

- (2) 2½" x 46½"
- (2) 11/2" x WOF; subcut
- (2) 1½" x 30½"

Fabric I, cut:

(6) 3½" x WOF; subcut (56) 3½" squares

All possible care has been taken to ensure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies.

Please read the instructions carefully before starting this project. If kitting it is recommended a sample is made to confirm accuracy.

Block Assembly

All seam allowances are ¼". Sew pieces right sides together. Press seam allowances open unless otherwise indicated.

 Draw a diagonal line on the wrong side of all Fabric E and Fabric I 3½" squares (Fig. 1).

Fig. 1



 Place (1) each marked Fabric E and Fabric I 3½" squares, right sides together, on opposite corners of (1) Fabric B 6½" square. Stitch on the marked lines, trim seam allowance to ¼", and press corners open. Repeat with (1) each marked Fabric E and Fabric I 3½" squares on the remaining corners to make (1) Block One (Fig. 2). Trim to measure 6½" square. Make a total of (12) Block One.




Fig. 2


 Repeat Step 2 using marked Fabric E and Fabric I 3¹/₂" squares and Fabric C 6¹/₂" squares to make Block Two (Fig. 3). Make a total of (6) Block Two.

Fig. 3




 Repeat Step 2 using marked Fabric E and Fabric I 3½" squares and Fabric A 6½" squares to make Block Three, noting orientation of the Fabric A square (Fig. 4). Make a total of (2) Block Three. Noting orientation of the Fabric A square, make (2) each Blocks Four, Five, and Six in the same manner.

Fig. 4



 Repeat Step 2 using marked (3) Fabric E, (1)
 Fabric I square, and Fabric D 6½" square to make (1) each Block Seven, Eight, Nine, and Ten, noting orientation of the Fabric D square and corner square placement in each block (Fig. 5).






Block Seven

Block Eight Block Nine

Block Ten





Quilt Top Assembly

Follow the Quilt Layout (page 6) while assembling the quilt top.

- Sew Fabric E 3" x WOF strips to opposite sides of the Fabric E 23½" x 42½" rectangle. Trim border strips even with panel top/ bottom. Sew Fabric E 3" x 28½" strips to top and bottom. Trim framed panel to measure 26½" x 46½".
- Sew Fabric H 2½" x 46½" strips to opposite sides of the framed panel. Sew Fabric H 1½" x 30½" strips to the top and bottom. Panel will measure 30½" x 48½".
- 8. Lay out (4) Block One, (2) Block Two, and (2) Block Four into a vertical row, noting fabric and block orientation. Join into a row and sew to the left side of the quilt center. In the same way, lay out (4) Block One, (2) Block Two, and (2) Block Five, then join and sew to the right side of the quilt center.
- 9. Lay out (2) each Block One and Block Three, and (1) each Block Two, Block Seven, and Block Eight into a horizontal row, noting fabric and block orientation. Join into a row and sew to the top of the quilt center. In the same way, lay out (2) each Block One and Block Six, and (1) each Block Two, Block Nine, and Block Ten, then join and sew to the bottom of the quilt center. Quilt center will measure 421/2" x 601/2".
- 10. Sew a **Fabric G** 1½" x 60½" strip to opposite sides of the quilt. Sew a **Fabric G** 1½" x 44½" strip to both the top and bottom.
- 11. Sew (1) **Fabric B** 4½" x 62½" strip to opposite sides of the quilt. Sew (1) **Fabric B** 4½" x 52½" strip to both the top and bottom. The quilt top will measure 52½" x 70½" unfinished.

Finishing

- Sew together the (7) 2¹/₂" x WOF
 Fabric E binding strips end to end using diagonal seams. Press the seams open. Press the binding strip in half, wrong sides together.
- 13. Layer the backing (wrong side up), batting, and quilt top (right side up). Baste the layers together and quilt as desired. Trim excess batting and backing even with the top of the quilt.
- 14. Leaving an 8" tail of binding and beginning along an edge of the quilt top, match raw edges of the binding to the raw edges of the quilt top. Sew the binding to the outside edge around all four sides and miter corners. Stop sewing approximately 12" from where you started and backstitch.
- 15. Lay both loose ends of binding flat along the quilt edge. Where these two loose ends meet, fold them back onto themselves and press to form a crease. Using this crease as your stitching line, sew the two open ends of the binding together, right sides matching. Trim seam to ¼" and press seam open. Finish sewing the binding to the quilt top.
- 16. Turn the binding over the raw edge to the back of the quilt and hand or machine stitch in place.



Quilt Layout

